

COMPUTER SIMULATIONS OF A COMMERCIAL BUILDING WITH TOP COOLING

Milos Lain¹, Jan Hensen²

¹Department of Environmental Engineering, Faculty of Mechanical Engineering, CTU in Prague, Czech Republic, lain@fsid.cvut.cz, tel:+420 22435 2586,

² Knowledge Center Building & Systems TNO-TU/e, Technische Universiteit Eindhoven, The Netherlands

ABSTRACT

In the introduction the application of low energy cooling method for commercial buildings in the middle Europe is discussed. The main part of the paper deals with modelling and simulation of building itself and HVAC system including control. The calibration of the ESP-r building model according to measured data is prescribed and problems with system simulation are discussed. The role of modelling and simulation for low energy cooling is presented on the conclusion.

BUILDING CONCEPT

The new headquarters for ČEZ, a.s. in Prague (1998 - 2002) is the first headquarters building in the Czech Republic to employ night-cooling and natural ventilation for most of the office spaces, supplementing part of the mechanical cooling and ventilation supply systems. During the initial design process computer simulation was applied to prove the chosen conception of night-cooling and natural ventilation. Occupied by ČEZ since April 2002, the new headquarters won the "Building of the Year" award by Czech foundation ABF in September 2002 (Dvorak 2002).




Figure 1 Visualization of the CAD model of the building




Figure 2 Principle of the daytime shading and nighttime forced ventilation

MEASUREMENTS

There are three different kind of measured data available. Firstly data provided from the control system of the building. Secondly the long time monitoring of the inside temperature and humidity and some more detail measurements of temperatures and velocity distribution inside the building and on the system diffusers. And finally outside climatic data from the CTU meteorological laboratory. All the three sets are used for calibration of the CEZ building model.




Figure 3 The building and its system monitoring

BUILDING MODEL

The ESP-r model of the 5 floor in the annex A was chosen to represent the problems in the big part of the building. One zone model including all detail structure description, shading properties and internal gains was set up. The geometry is simplified on a few points. At the first few internal office blocks and toilets block which are separated from the rest of the floor by internal walls are not consider as different zones because of the same type of control of this blocs as the rest of the office area and the influence if the thin and light internal walls is negligible.




Figure 4 The ESP-r model of the 5th floor of the building

BUILDING MODEL CALIBRATION

The ESP-r model calibration is very important part of the real building modelling. The aim of the calibration is set up the not certain inputs to the building model according to measured performance of the building. Calibrated model ca be used to predict performance of the building for different condition, for example to optimise the system control strategy.

For most office buildings the internal gains from office equipment are the most important parameter. The are two reasons. Firstly for well insulated and shaded building the internal gains represents biggest part of all gains. Secondly real performance data are never available. Previous research (Duška 2004) shows the rate of real average power consumption (heat production) to nominal (nameplate) is from 5 to 60 percent for office equipments.




Figure 5 Comparison of the building measurements and simulation results set 1




Figure 6 Comparison of the building measurements and simulation results set 2




Figure 7 Comparison of the building measurements and simulation results set 3

System comparison




Figure 8 Comparison of the system measurements and simulation results set 1

CONCLUSION

The ESP-r simulation results analysis performed within calibration point out the following issues. The heat transfer coefficients model play the important role for the simulation. When standard heat transfer was used the energy consumption and load profile are more close to measured, but the inside surface wall temperatures are high. If the increased heat transfer is applied the wall temperatures are close to air temperatures, but the load profile and consumption for building simulation diverse from measured. To be able to find proper solution additional measurements will be done this summer, to find out the surface temperatures inside office.

Simulation of the building including the air-conditioning system finally agree better with measurements but, there are few problems with some fluctuations and difficulties with system simulation using ESP-r plant simulation.

ACKNOWLEDGMENT

This research was supported by Research proposal U12116 -11101

REFERENCES

- Santamouris, M., Asimakopoulos, D., 1996, *Passive Cooling of Buildings*, James & James Ltd., London, U.K., 472 p.
- Barnard, N., Jaunzens, D., 2001, *Low Energy Cooling – Technology Selection and Early Design Guidance*, Building Research Establishment Ltd, London, 109 p.
- Liddament, M.W., 2000, *Low energy cooling*, ESSU, Coventry, U.K., 32 p.
- Roel, H., 2000, *Low Energy Cooling – Detailed Design Tools*, Building Research Establishment Ltd, London, 327 p.
- 1995, *Review of Low Energy Cooling Technologies*, Natural resources Canada, Ottawa, Canada, 88 p.
- Lain, M., 2002, Pôčítacové simulace při řešení alternativních způsobů chlazení budov, *Proc. Simulace budov a techniky prostředí 2002*, IBPSA-CZ, p. 93 to 96.
- Dvorak, J., 2002, Hlavní správa CEZ: noční chlazení, *Proc. Simulace budov a techniky prostředí 2002*, IBPSA-CZ, p. 15 to 17.
- Drkal, F., Jelen, M., Lain, M., Mareš, L., 2002, "Posudek klimatizačního systému kanceláře C v objektu Vodní stavby bohemia", Internal report CTU, 2002, 24 p.+13 p.